

# Specifications



Photo is representative



## Eaton 5E700D

Eaton 5E Gen2 UPS DIN, 700 VA, 360 W,  
Input: Schuko, Outputs: (2) DIN, Tower

### General Specifications

|                      |                                                                                                                        |
|----------------------|------------------------------------------------------------------------------------------------------------------------|
| PRODUCT NAME         | Eaton 5E Gen2 UPS                                                                                                      |
| CATALOG NUMBER       | 5E700D                                                                                                                 |
| PRODUCT LENGTH/DEPTH | 288 mm                                                                                                                 |
| PRODUCT HEIGHT       | 148 mm                                                                                                                 |
| PRODUCT WIDTH        | 100 mm                                                                                                                 |
| PRODUCT WEIGHT       | 4.29 kg                                                                                                                |
| COMPLIANCES          | CB<br>LVD Directive<br>EMC Directive<br>RoHS Directive<br>Packaging Directive<br>WEEE Directive<br>Batteries Directive |
| CERTIFICATIONS       | IEC/EN 62040-1<br>IEC/EN 62040-2<br>CE<br>EAC<br>Ukr<br>IEC/EN 62040-3<br>UKCA<br>Cm                                   |
| EAN                  | 3553340704147                                                                                                          |



Powering Business Worldwide

## Product specifications

### SPECIAL FEATURES

- Automatic Voltage Regulation (AVR)
- Saves space with a compact tower design
- Includes two Schuko (DIN) Outlets

|                   |                     |
|-------------------|---------------------|
| TOPOLOGY          | Line-interactive    |
| FORM FACTOR       | Tower               |
| CONSTRUCTION TYPE | Free standing model |
| COLOR             | Black               |
| VA RATING         | 700 VA              |
| WATTAGE           | 360 W               |
| RACK MOUNTING KIT | No                  |

### PACKAGE CONTENTS

- Quick start
- Safety instructions

|                            |                             |
|----------------------------|-----------------------------|
| SURGE PROTECTION           | Yes                         |
| INTERNAL BYPASS            | No                          |
| HOT SWAP POWER             | No                          |
| AUTO SHUTDOWN FUNCTION     | No                          |
| PRIMARY FREQUENCY - MAX    | 63 Hz                       |
| PRIMARY FREQUENCY - MIN    | 45 Hz                       |
| INPUT CONNECTION           | Protective contact (SCHUKO) |
| INPUT CORD LENGTH          | 1.2 m                       |
| INPUT NOMINAL VOLTAGE      | 230V default (220/230/240V) |
| NOMINAL FREQUENCY          | 50/60 Hz                    |
| INPUT FREQUENCY RANGE      | 45-63 Hz                    |
| RECEPTACLE                 | (2) Schuko                  |
| NUM OF OUTPUTS PC (SCHUKO) | 2                           |
| VOLTAGE                    | 230V                        |
| OUTPUT NOMINAL VOLTAGE     | 230V                        |
| FEED TYPE                  | 1                           |
| VOLTAGE TYPE               | AC                          |

## Resources

### BROCHURES

[eaton-dpq-5egen2-ups-quickstartguide-en-gb.pdf](#)

### CERTIFICATION REPORTS

[eaton-dpq-5egen2-ups-certificate-en-gb.pdf](#)

### MANUALS AND USER GUIDES

[eaton-dpq-5egen2-ups-manual-en-gb.pdf](#)

### TECHNICAL DATA SHEETS

[eaton-dpq-5egen2-ups-datasheet-en-gb.pdf](#)

|                                      |                                                                             |
|--------------------------------------|-----------------------------------------------------------------------------|
| <b>RUNTIME GRAPH</b>                 | <a href="#">View runtime graph</a>                                          |
| <b>BATTERY MANAGEMENT</b>            | Automatic battery test,<br>deep-discharge protection,<br>cold-start capable |
| <b>BATTERY RATING</b>                | 12 V / 7 Ah                                                                 |
| <b>BATTERY TYPE</b>                  | Sealed, lead-acid                                                           |
| <b>EXTENDED BATTERY CAPABILITY</b>   | No                                                                          |
| <b>EXPANSION SLOTS</b>               | No                                                                          |
| <b>ETHERNET INTERFACE</b>            | No                                                                          |
| <b>INCLUDES NETWORK CARD</b>         | No                                                                          |
| <b>USER INTERFACE</b>                | LEDs                                                                        |
| <b>TYPE OF INTERFACE</b>             | None                                                                        |
| <b>POTENTIAL FREE SWITCH CONTACT</b> | No                                                                          |
| <b>RELATIVE HUMIDITY</b>             | 0-90% non-condensing                                                        |
| <b>TEMPERATURE RANGE</b>             | 0° to 40°C (32° to 104°F)                                                   |
| <b>OPERATING TEMPERATURE - MAX</b>   | 40 °C                                                                       |
| <b>OPERATING TEMPERATURE - MIN</b>   | 0 °C                                                                        |
| <b>OUTPUT APPARENT POWER</b>         | 700 VA                                                                      |
| <b>INPUT VOLTAGE - MAX</b>           | 300 V                                                                       |
| <b>INPUT VOLTAGE - MIN</b>           | 140 V                                                                       |
| <b>OUTPUT VOLTAGE - MAX</b>          | 257 V                                                                       |
| <b>OUTPUT VOLTAGE - MIN</b>          | 195 V                                                                       |
| <b>SECONDARY FREQUENCY - MAX</b>     | 60 Hz                                                                       |
| <b>SECONDARY FREQUENCY - MIN</b>     | 50 Hz                                                                       |
| <b>BATTERY QUANTITY</b>              | 1                                                                           |
| <b>EFFICIENCY AT MAX. LOAD</b>       | 95                                                                          |
| <b>INPUT VOLTAGE RANGE</b>           | 140-300 V                                                                   |
| <b>OUTPUT FREQUENCY</b>              | 50/60 Hz                                                                    |
| <b>OUTPUT VOLTAGE RANGE</b>          | 195-257 V                                                                   |
| <b>PHASE (INPUT)</b>                 | 1                                                                           |
| <b>PHASE (OUTPUT)</b>                | 1                                                                           |

|                 |
|-----------------|
| PROJECT NAME:   |
| PROJECT NUMBER: |
| PREPARED BY:    |
| DATE:           |



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

