

# Spécifications

## Eaton EBAB338

Eaton G3+ Basic Rack PDU, 0U, 42U, IEC-60309 input, 44,6 kW, 63A, 346-415V, Outlets: (21) C13, (12) C19



La photo est représentative



### Spécifications générales

|                      |                                    |
|----------------------|------------------------------------|
| PRODUCT NAME         | Eaton Rack PDU G4                  |
| CATALOG NUMBER       | EBAB338                            |
| EAN                  | 3553340696893                      |
| PRODUCT LENGTH/DEPTH | 1829 mm                            |
| PRODUCT HEIGHT       | 52 mm                              |
| PRODUCT WIDTH        | 65 mm                              |
| PRODUCT WEIGHT       | 9.5 kg                             |
| COMPLIANCES          | RoHS Compliant<br>CE Marked<br>EAC |
| CERTIFICATIONS       | CE<br>IEC 60950-1<br>EN 55024:2010 |

## Spécifications du produit

### SPECIAL FEATURES

- Built-in IEC outlet eGrip retention, retains all standard IEC plugs
- Built-in outlet P-lock system, locking mechanism with P-lock power cords
- 60°C Operating temperature
- Colour-coded outlet and branch circuits for simple load balancing
- Hydraulic-Magnetic Circuit Breakers with accidental trip protection
- Low-profile form factor: 52 mm wide x 53 mm deep on most models
- Universal mounting system: Button mounting on rear and side + variable mounting system

|                |                |
|----------------|----------------|
| TYPE           | Basic Rack PDU |
| FORM FACTOR    | 0U (Vertical)  |
| OUTLET CONTROL | No             |

### PACKAGE CONTENTS

- Rack PDU
- Mounting accessories
- Quickstart guide
- Safety Instructions

|                       |                           |
|-----------------------|---------------------------|
| OPERATING TEMPERATURE | 0° to 60°C (32° to 140°F) |
| MOUNTING DIRECTION    | Vertical                  |
| COLOR                 | Black                     |
| MATERIAL              | Aluminium                 |
| INPUT CONNECTION      | IEC-60309 63A 3Ph         |
| CORD LENGTH           | 3m                        |
| WATTAGE               | 43.6 kW max               |
| AMPERAGE RATING       | 32 A                      |
| INPUT VOLTAGE         | 346-415V                  |
| PHASE                 | Three-phase               |

## Ressources

### DECLARATIONS OF CONFORMITY

[EU declaration of conformity Rack PDU G4](#)

|                                   |                           |
|-----------------------------------|---------------------------|
| FREQUENCY RATING                  | 50/60 Hz                  |
| OUTLETS                           | (21) C13, (12) C19        |
| NUMBER OF OUTPUTS C13             | 21                        |
| NUMBER OF OUTPUTS C19             | 12                        |
| NUMBER OF OUTLETS WITH EARTH PIN  | 33                        |
| CIRCUIT BREAKER                   | (12) single-pole          |
| SNMP                              | No                        |
| ETHERNET INTERFACE                | No                        |
| SERIAL INTERFACE                  | No                        |
| MASS CONFIGURATION                | No                        |
| ELECTRICAL CONNECTION             | Connecting cord with plug |
| MOUNTING DIMENSION (METRICAL)     | 52                        |
| MOUNTING DIMENSION (STANDARDIZED) | Metric                    |
| SWITCHABLE                        | No                        |
| OVER VOLTAGE CATEGORY             | 2                         |
| FITTED WITH:                      | Mounting material         |
| SERIES                            | G3+                       |

|                 |
|-----------------|
| PROJECT NAME:   |
| PROJECT NUMBER: |
| PREPARED BY:    |
| DATE:           |



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Irlande  
Eaton.com

Follow us on social media to get the latest product and support information.

