## Specifications



Photo is representative





## Eaton EL500IEC

Eaton Ellipse ECO UPS IEC, 500 VA, 300 W, Input: C14, Outputs: (3) C13, (1) C13 surge only, Tower

General Specifications	
PRODUCT NAME	Eaton Ellipse ECO UPS
CATALOG NUMBER	EL500IEC
PRODUCT LENGTH/DEPTH	81 mm
PRODUCT HEIGHT	263 mm
PRODUCT WIDTH	235 mm
PRODUCT WEIGHT	2.9 kg
COMPLIANCES	CE Marked
CERTIFICATIONS	IEC/EN 62040-1 IEC/EN 62040-2 CE EAC
EAN	3553340620539
UPC	786680224812



Battery	
BATTERY TYPE	Sealed, lead-acid
RUNTIME GRAPH	View runtime graph
BATTERY REPLACEMENT	User replaceable
BATTERY QUANTITY	1
BATTERY MANAGEMENT	Replaceable batteries, Automatic battery test, deep-discharge protection, cold-start capable
BATTERY RATING	12 V / 4.5 Ah
EXTENDED BATTERY CAPABILITY	No

Electrical output	
RECEPTACLE	(3) C13, (1) C13 surge only
VOLTAGE	230V
WATTAGE	300W
OUTPUT POWER FACTOR	0.6
OUTPUT VOLTAGE RANGE	184-264 V (adjustable to 161-284 V)
OUTPUT NOMINAL VOLTAGE	230V default (220/230/240V)
FEED TYPE	1
TOPOLOGY	Offline
VA RATING	500 VA

Electrical input	
INPUT CONNECTION	C14
INPUT NOMINAL VOLTAGE	230V default (220/230/240V)
NOMINAL FREQUENCY	50/60 Hz
INPUT VOLTAGE RANGE	184-264 V (adjustable to 161-284 V)
INPUT FREQUENCY RANGE	46-70 Hz

Communications	
INCLUDES NETWORK CARD	No
ETHERNET INTERFACE	No
USER INTERFACE	LEDs
POTENTIAL FREE SWITCH CONTACT	No
EXPANSION SLOTS	No
TYPE OF INTERFACE	None

Environmental	
ALTITUDE	2000 m
NOISE LEVEL	<25 dB at 1 meter
TEMPERATURE RANGE	0° to 35°C (32° to 95°F)
RELATIVE HUMIDITY	0-85% non-condensing

Additional specifications	
CONSTRUCTION TYPE	Free standing model
PACKAGE CONTENTS	<ul><li>(2) IEC-IEC cables</li><li>User manual</li><li>Safety instructions</li></ul>
PHASE (OUTPUT)	1
AUTO SHUTDOWN FUNCTION	No
COLOR	Black
EFFICIENCY AT MAX. LOAD	98
RACK MOUNTING KIT	No
PHASE (INPUT)	1
SURGE PROTECTION	Yes

Resources	
BROCHURES	Eaton UPS and battery services - EN  Eaton UPS Services Quick Guide - EN
COMPLIANCE INFORMATION	EU declaration of conformity Eaton Ellipse ECO
MANUALS AND USER GUIDES	Eaton Ellipse ECO UPS - 500/650/800/1200/1600 - Installation and user manual (multiple languages)
TECHNICAL DATA SHEETS	Datový list UPS EllipseECO  Eaton Ellipse ECO UPS - 500/650/800/1200/1600  VA - Datasheet

**PROJECT NAME: PROJECT NUMBER: PREPARED BY:** DATE:



**Eaton Corporation plc** 

Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

 $\hbox{@ 2025 Eaton.}$  All Rights Reserved.

Follow us on social media to get the latest product and support information.









