

Specifications



Photo is representative

Eaton MBP6KI

Eaton HotSwap MBP maintenance bypass,
6000 VA, Input: Hardwired, 200-240V,
Outlets: (3) C13, (2) C19, Hardwired

General specifications

PRODUCT NAME	Eaton HotSwap MBP maintenance bypass
CATALOG NUMBER	MBP6KI
UPC	743172040145
PRODUCT LENGTH/DEPTH	185 mm
PRODUCT HEIGHT	150 mm
PRODUCT WIDTH	305 mm
PRODUCT WEIGHT	3.28 kg
COMPLIANCES	CE Marked
CERTIFICATIONS	CE
MODEL CODE	Eaton HotSwap MBP 6000i

Product specifications

TYPE	Hotswap MBP
FORM FACTOR	3U
OUTLET CONTROL	No
PACKAGE CONTENTS	<ul style="list-style-type: none">• Maintenance Bypass• Cable locking system• Connection cable to the UPS• Rack-mounting kit• User manual
OPERATING TEMPERATURE	0° to 40°C (32° to 104°F)
MOUNTING DIRECTION	Horizontal
COLOR	Black
INPUT CONNECTION	Other
VA RATING	6000 VA
INPUT VOLTAGE	200-240V
PHASE	Single-phase
OUTLETS	(3) C13,(2) C19, Hardwired
NUMBER OF OUTPUTS C13	3
NUMBER OF OUTPUTS C19	2
NUMBER OF OUTPUTS HARDWIRED	1
NUMBER OF OUTLETS WITH EARTH PIN	5
SNMP	No
ETHERNET INTERFACE	No
SERIAL INTERFACE	No
MASS CONFIGURATION	No
ELECTRICAL CONNECTION	Screwed terminal
MOUNTING DIMENSION (METRICAL)	150
MOUNTING DIMENSION (STANDARDIZED)	482.6 mm (19 inch)
SWITCHABLE	No
OVER VOLTAGE CATEGORY	2
FITTED WITH:	Mounting material LED indication

Resources

BROCHURES	Eaton UPS and battery services - EN
	Eaton UPS Services Quick Guide - EN
COMPLIANCE INFORMATION	EU declaration of conformity Eaton 9PX UPS

COMMUNICATION	No
---------------	----

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

