

HARDWARE FEATURES

Interface	<ul style="list-style-type: none">• 24× 10/100/1000 Mbps PoE+ RJ45 Ports (support 802.3af PoE and 802.3at PoE+)• 2× 10/100/1000 Mbps RJ45 Port• 2× Gigabit SFP Slot• Auto-Negotiation/Auto MDI/MDIX
Fan Quantity	2
Installation	Rackmountable
Physical Security Lock	√
Power Supply	100–240V AC, 50/60Hz
PoE Ports (RJ45)	<ul style="list-style-type: none">• Standard: 802.3af PoE and 802.3at PoE+ compliant• PoE Ports: 24 ports• PoE Budget: 384W available for all PoE+ ports, 30W max per port• Fast PoE & Perpetual PoE• PoE Auto Recovery[†]• Up to 250m PoE transmission distance^{**}
Dimensions (W x D x H)	17.3 × 13.0 × 1.7 in.(440 × 330 × 44 mm)
Surge Protection	±6kV

PERFORMANCE

Switching Capacity	56 Gbps
Packet Forwarding Rate	29.76 Mpps
MAC Address Table	8K

PERFORMANCE

Packet Buffer Memory4 Mbit

Jumbo Frame15 KB

SOFTWARE FEATURES

Quality of Service

- Port-based/802.1p/DSCP QoS
- 8 Priority Queues
- Priority Schedule Mode
- WRR (Weighted Round Robin)
- Queue Weight Config
- Bandwidth Control
- Port-Based Rating Limit
- Storm Control
- Multiple Control Modes (kbps/pps)
- Broadcast/Multicast/Unknown-Unicast Control[△]

L2 Features

- Static Link Aggregation
- Loop Prevention / Loopback Detection
- Flow Control
- 802.3x Flow Control
- Mirroring
- Port Mirroring
- One-to-One
- Many-to-One
- Ingress/Egress/Both
- Port Statistics
- Port Mirror Status
- Traffic Statistics
- 802.1ab LLDP

L2 Multicast

- IGMP Snooping
- IGMP v1/v2/v3 Snooping
- Fast Leave

VLAN

- MTU VLAN
- Port-Based VLAN
- 802.1Q Tag VLAN

SOFTWARE FEATURES

- Max 32 VLAN Groups
- 4K VID

Transmission Method

Store-And-Forward

MANAGEMENT FEATURES

Omada App
Yes. Requires the use of Omada Hardware Controller, Omada Cloud-Based Controller, or Omada Software Controller.

Centralized Management

- Omada Cloud-Based Controller
- Omada Hardware Controller
- Omada Software Controller

Cloud Access

Yes. Requires the use of Omada Hardware Controller, Omada Cloud-Based Controller, or Omada Software Controller.

Zero-Touch Provisioning

Yes. Requires the use of Omada Cloud-Based Controller

Management Features

- Web-based GUI
- DHCP Client
- Cable Diagnostics
- Automatic Device Discovery[†]
- Batch Configuration[†]
- Batch Firmware Upgrading[†]
- Unified Configuration[†]

OTHERS

Certification

FCC, CE, RoHS

Package Content

- ES228GMP
- Power Cord
- Mounting Brackets
- Rubber Feet

OTHERS

- Screws
- Installation Guide

Environment

- Operating Temperature: -5°C~45°C (23°F~113°F)
- Storage Temperature: -40°C~70°C (-40°F~158°F)
- Operating Humidity: 10%~90% non-condensing
- Storage Humidity: 5%~90% non-condensing