

HARDWARE FEATURES

Standards and Protocols	IEEE 802.3, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x, IEEE 802.3af, IEEE 802.3at
Interface	• 6*10/100 Mbps RJ45 Ports with 4 PoE+ Ports (Port 1 to Port 4) • AUTO Negotiation/AUTO MDI/MDIX
Network Media	• 10BASE-T: UTP category 3, 4, 5 cable (maximum 100m) • 100BASE-TX: UTP category 5 or above cable (maximum 100m)
Fan Quantity	Fanless
External Power Supply	External Power Adapter (Output: 53.5 VDC / 1.31 A)
Power Input	220~240V, 50/60Hz (NV)
LED	Power, Link/Act, PoE Status
Packet Forwarding Rate	0.893 Mpps
PoE Ports (RJ45)	Standard: 802.3 af/at compliant PoE Ports: Port 1- Port 4 Power Supply: 65 W
Dimensions (W x D x H)	3.9×3.9×1.0 in (99.8×98×25 mm)
Max. Power Consumption	66.53 W
Max Heat Dissipation	226.19 BTU/h

PERFORMANCE

Switching Capacity	1.2 Gbps
Packet Buffer Memory	2048 Bytes
Advanced Features	• Extend Mode (Ports 1-4) • Isolation Mode (Ports 1-4) • PoE Auto Recovery (Ports 1-4)
Jumbo Frame	2 KB

SOFTWARE FEATURES

MAC Address Table	2K
Transmission Method	Store-And-Forward

OTHERS

Package Content	Switch, Power Adapter, Rubber Feet, Installation Guide
Certifications	CE, ROHS, KC, NTRA
Environment	• Operating Temperature: 0°C to 40 °C (32 °F to 104°F) • Storage Temperature: -40 °C to 70 °C (-40 °F to 158°F) • Operating Humidity: 10% to 90% non-condensing • Storage Humidity: 5% to 90% non-condensing