



USB Type-C 6-in-1 Hub

Bridge Devices, Expand Connections

UH6120C



1× HDMI
4K@60Hz



1× PD
100W



1× RJ45
1 Gbps



USB-C/2× USB-A
5 Gbps

Highlights



Plug & Play
For Various Operating Systems†




Convenient & Stylish
Self-Storage for Connector

Bridge Devices, Expand Connections



4K

HDMI
Ultra High-Definition
Media Display



RJ45 GE
Stable Gigabit
Connection



PD 3.0
Powerful 100W
Fast Charging



USB 3.0
5 Gbps SuperSpeed
Data Transfer



**Scratch
Resistant**
Aluminum Alloy Case



**Durable
Design**
Braided Cable

Specifications

Hardware

- **Interface:**
 - 1× PD 100W Charging
 - 1× USB Type-C 5Gbps
 - 2× USB Type-A 5Gbps
 - 1× HDMI 4K@60Hz
 - 1× RJ45 1Gbps
- **Connector:**
 - 1× USB Type-C
- **PD Input:**
 - 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/5A
- **USB-C Connector Input:**
 - 5V/3A

Physical

- **Dimension (W×D×H):**
 - 4.65 × 1.69 × 0.56 in (118.2 × 43 × 14.3 mm)
- **Case:**
 - Aluminum Alloy Case
- **Cable:**
 - 180mm Braided Cable
- **Package Contents:**
 - 1× UH6120C
 - 1× Quick Installation Guide

Others

- **Supported Systems:**
 - Mac OS X 10.9 and later, Windows (7 and later), Linux OS, iPad OS, iOS, Android, and Chrome OS
- **Plug & Play:**
 - USB-C PD port, USB-C port, HDMI port, USB-A ports, Gigabit Ethernet port.*
 - The gigabit Ethernet port may require installing a driver for compatibility with certain older operating systems. Please visit our official website at www.tp-link.com to download the necessary driver for these systems:
 - Windows 7/8
 - Mac OS X 10.9 to 10.15
- **Certification:** CE, FCC, RoHS, HDMI, BSMI
- **Environment:**
 - Operating Temperature: 0°C~40°C (32°F~104°F)
 - Operating Humidity: 10%~90% non-condensing
 - Storage Humidity: 5%~90% non-condensing



For more information, please visit

https://www.tp-link.com/products/details/?model=UH6120C_V1

or scan the QR code left

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Specifications are subject to change without notice. All the brands and product names are trademarks or registered trademarks of their respective holders.

*Port transmission specifications are the testing result conducted by TP-Link laboratory. Actual transfer rate is not guaranteed and will vary as a result of device conditions and environmental factors.

†Plug and Play for Mac OS X El Capitan Version 10.11.6 and later, Windows 11/10/8.1, Linux OS, iPad OS, iOS, Android, and Chrome OS. More OS versions will be supported soon.

‡To ensure compatibility, you may need to update the hub's drivers after an OS update. You can find our latest drivers in the download center at tp-link.com/en/download-center.

©2025 TP-Link

www.tp-link.com

TP-Link USB Type-C 6-in-1 Hub UH6120C